

CW-10EX

POWERFULL MOBILITY



Video

SERVICES IN FRANCE

NO COMPROMISE - YOU CAN HAVE IT ALL ATEX CERTIFIED, YET COMPACT AND POWERFUL

ATEX certification : Exib II 2G Ex ib IIB T4 Gb

- Processor HELIO P60 Octo Core 2.00GHz
- Android 13
- MIL STD 810G standard tested, drop resistance 1.2m
- IP65
- Sunlight readable, 1000 nits
- Operating temperature: -20°C +55°C
- Standard battery 14600mAh
- Rear handle
- 4G LTE multi-carrier with GPS





1. USB Type-A
2. RS232
3. Speaker
4. Front camera
5. Ambient light sensor
6. LED charge
7. Menu button
8. Back button
9. Home button
10. Search button
11. Function key 1
12. Function key 2
13. Direction key
14. Confirmation key
15. Microphone
16. Docking Connector
17. Power button
18. Micro SD/SIM card slot
19. USB-Type-C
20. Main camera
21. Temperature sensor (optional)

PRODUCT SPECIFICATIONS

SOFTWARE	Android 13
DURABILITY	ATEX certified: Exib II 2G Ex ib IIB T4 Gb MIL-STD-810G (multiple drops 1.2 m) 26 times on each corner and each side with the same shelf in operation IP65 RATING Screen protection
CPU	Processeur HELIO P60 Octo Core 2.00 GHz
RAM	8GB
STORAGE	128GB
DISPLAY	10.1" HD 720*1280 HD industrial 1000 nits Sunlight readable
AUDIO	1 microphone 1 built-in speaker
SCREEN	Capacitive 5-point multi-touch screen and stylus, glove and rain mode
INTERFACES	USB Type-C, USB Type-A SIM card slot 1.8/3.3V Micro SD card slot; max 128GB
CAMERAS	5MP front camera 13MP rear camera, flash LED flash

WIRELESS	4G LTE module GSM function GPS / Glonass / Beidou / AGPS Dual-band WIFI (2.4GHz/5GHz) single stream 802.11 a/b/g/n/ac Bluetooth® 4.2 Low Energy (LE)
POWER SUPPLY	Batterie : 14600mAh AC power: 5V, 2A-10W
SENSORS	MEMS sensors on 9 axes (accelerometer, compass, gyroscope) Ambient light sensor Proximity sensor
DIMENSIONS	320 x 228 x 12 mm
WEIGHT	1360 g
ACCESSORIES	Rear handle Mobile docking station Additional charger
TEMPERATURE	Operating temperature -20°C to 55°C Storage temperature -40°C to 80°C