

# CW-6EX



# NEW



Video

**SERVICES IN FRANCE**

## MOBILE TERMINAL DESIGNED FOR TRACEABILITY ATEX CERTIFIED, YET COMPACTE AND POWERFUL

ATEX certification : Ex II 2G Ex ib IIB T4 Gb

- Android 11
- ARM Cortex A73 Octa-core (2.0GHz)
- Tested to standard MIL STD 810G, drop resistance 1.2m
- IP67
- 3G/4G LTE
- NFC/Barcode 2D reader : optional
- Fingerprint reader : optional
- Handstrap
- Battery autonomy : up to 15 hours





- ① Power button
- ② SOS button
- ③ Type C (Sealed Cover)
- ④ Earphone (Sealed Cover)
- ⑤ RS232 (optional)
- ⑥ Barcode module (optional)
- ⑦ SMA (optional)
- ⑧ Hanging Hole
- ⑨ Front camera
- ⑩ Charge lamp
- ⑪ Receiver
- ⑫ Light sensor
- ⑬ Delete button
- ⑭ Custom button
- ⑮ Home button
- ⑯ Confirm button
- ⑰ Menu button
- ⑱ Fingerprint module (optional)
- ⑲ Back button
- ⑳ Arrow button
- ㉑ Search button
- ㉒ MIC
- ㉓ 2 pin pogo pin
- ㉔ Volume up
- ㉕ Volume down
- ㉖ Scan button
- ㉗ SIM (Sealed Cover)
- ㉘ Nameplate
- ㉙ Main camera
- ㉚ Flash light
- ㉛ Speaker

## PRODUCT SPECIFICATION

<b>SOFTWARE</b>	Android 11
<b>DURABILITY</b>	MIL-STD-810G (Multiple 4' / 1.2m Drops) 26 times all corners and sides with single tablet while operating IP67 (IEC 60529) 500 times x 1m tumble test Gorilla Glass
<b>CPU</b>	ARM Cortex A73 Octa-core (2.0GHz)
<b>MEMORY</b>	8GB
<b>STORAGE</b>	128 GB
<b>DISPLAY</b>	5,5" - 1080 x 1920 IPS/AFFS 1000 Nits sunlight readable
<b>AUDIO</b>	1 digital microphone 1 integrated speaker
<b>SCREEN</b>	Glove and rain use mode
<b>INTERFACES</b>	Docking connector Micro USB-C Power supply connector Audio Jack 3.5mm Dual SIM card reader Micro SDXC card reader max. 256GB

<b>CAMERA</b>	Front camera : 5MP Auto focus, flash Rear camera : 13MP (AF) led flash
<b>WIRELESS</b>	4G/LTE GPS Wi-Fi 802.11a/b/g/n/ac Bluetooth® 4.2 low energy (LE)
<b>POWER SUPPLY</b>	External battery 5V, 7800 mAh Battery autonomy - up to 15 hours
<b>SENSORS</b>	NFC/Barcode 2D reader : optional Fingerprint reader : optionnal Compass, accelerometer, gyroscope Ambient light sensor Proximity sensor
<b>DIMENSIONS</b>	195mm x 98mm x 22mm
<b>WEIGHT</b>	460g
<b>TEMPERATURE</b>	Operating temperature -20°C to 55°C  Storage temperature -40°C to 80°C

